

SAFETY DATA SHEET

SECTION 1	PRODUCT AND COMPANY IDENTIFICATION		
Trade Name:	K-Mag®, all grades		
Chemical Name:	Potassium Magnesium Sulfate		
CAS Number:	14977-37-8		
Chemical Family:	Inorganic Salt		
Synonyms:	Potassium Magnesium Sulfate SPM Langbeinite Sulfate of Potash Magnesia		
Primary Use:	Crop nutrient		
Company Information:	THE MOSAIC COMPANY 3033 Campus Drive Plymouth, MN 55441 www.mosaicco.com 800-918-8270 or 763-577-2700 8 AM to 5 PM Central Time US		
Emergency Telephone:	800-918-8270 or 763-577-2700 8 AM to 5 PM Central Time US 24 Hour Emergency Telephone Number: For Chemical Emergencies: Spill, Leak, Fire or Accident Call CHEMTREC North America: (800) 424-9300 Others: (703) 527-3887 (collect)		

SECTION 2	HAZARD IDENTIFICATION		
GHS Classification:	Not Applicable		Not Applicable
	Signal Word: not applicable Hazard Statement(s) Not applicable		
Label Elements:			
Prevention:	Not applicable		
Response:	Not applicable Not applicable		
Storage:	Not applicable Not applicable		
Disposal:	Not applicable Not applicable		

SECTION 3	COMPOSITION INFORMATION ON INGREDIENTS			
Formula:	K2 SO4 · 2MgSO4			
Composition:	Potassium Magnesium Sulfate (Langbeinite) Sodium Chloride	CAS 14977-37-8 CAS 7647-14-5	94.5-99.5%	

Status: Revised Section(s) Revised: All Revision Date: 06/01/2015 Page 1 of 6



SECTION 4	FIRST AID MEASURES		
	Eyes:	Move victim away from exposure and into fresh air. Flush eyes with plenty of clean water for at least 15 minutes. If symptoms persist, seek medical attention.	
First Aid Procedures:	Skin:	Wash contaminated area thoroughly with mild soap and water. If chemical or solution soaks through clothing, remove clothing and wash contaminated skin. If irritation develops and persists after washing, seek medical attention.	
	Inhaled:	If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention.	
	Ingestion:	If large amounts are swallowed, seek emergency medical attention. If possible, do not leave victim unattended and observe closely for adequacy of breathing.	
Note to Physician:	None Known		

SECTION 5	FIRE FIGHTING MEASURES		
Extinguishing Media:	Use extinguishing agent suitable for type of surrounding fire.		
Protection of Firefighters:	No unusual fire or explosion hazards are expected. Combustion can yield oxides of sulfur when heated above 1000°F (537°C).		
	Positive pressure, self-contained breathing apparatus is required for all firefighting activities involving hazardous materials. Full structural firefighting (bunker) gear is the minimum acceptable attire. The need for proximity, entry, flashover and/or special chemical protective clothing (see Section 8) needs to be determined for each incident by a competent firefighting safety professional.		
	Water used for fire suppression and cooling may become contaminated. Discharge to sewer system(s) or the environment may be restricted, requiring containment and proper disposal of water (see Section 6).		

SECTION 6	ACCIDENTAL RELEASE MEASURES		
Response Techniques:	Stay upwind and away from spill (dust hazard). Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Notify appropriate federal, state, and local agencies as may be required (see Section 15). Minimize dust generation. Sweep up and package appropriately for disposal. Large spills can harm or kill vegetation.		

SECTION 7	HANDLING AND STORAGE		
Handling:	The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see Section 8). Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing or shoes. Use good personal hygiene practices.		
Storage:	Use and store this material in dry, well-ventilated areas. Store only in approved containers. Keep container(s) tightly closed. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Material may absorb moisture from the air.		

Status: Revised Section(s) Revised: All Revision Date: 06/01/2015 Page **2** of **6**



SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION			
Engineering Controls:	Use process enclosure, general dilution ventilation or local exhaust systems where necessary to maintain airborne dust concentration below the OSHA standards or in accordance with applicable regulations.			
	Eye/Face: Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended.			
	Skin:	The use of cloth or leather work gloves is advised to prevent skin contact, possible irritation and absorption.		
Personal Protective Equipment (PPE):	Respiratory: Other:	A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator. A source of clean water should be available in the work area for		
		flushing eyes and skin	1.	
General Hygiene Considerations:	Wash thoroughly after handling Use adequate ventilation			
Exposure Guidelines:	OSHA Permissible Exposure Limits (PEL):		Particulates Not Otherwise Regulated: 5 mg/m³ TWA (respirable); 15 mg/m³ TWA (total)	
Exposure Guidelines.	ACGIH Threshold Limit Value (TLV):		Particulates Not Otherwise Specified: 3 mg/m ³ TWA (respirable); 10 mg/m ³ TWA (inhalable)	

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES			
Note: Unless otherwise stated, values in this section are determined at 20°C (68°F) and 760 mm Hg (1 atm).				
Appearance:	White and pink to gray, crystalline or granular	Vapor Pressure (mm Hg):	Not applicable	
Odor:	None	Vapor Density (air=1):	Not applicable	
Odor Threshold:	No data available	Specific Gravity or Relative Density:	2.81 – 2.85	
Physical state:	Crystalline or granular solid	Bulk Density:	Loose 83 - 94 lbs/ft ³ (1300 - 1505 kg/m ³);	
pH:	Approx. 7 in a 5% solution	Solubility in Water:	Approximately 24.4% @ 77°F (25°C)	
Melting Point/ Freezing Point:	972°C (1700°F)	Partition coefficient:	No data available	
Boiling Point:	Not applicable	Auto-Ignition Temperature:	Not applicable	
Flash Point:	Not applicable	Decomposition Temperature:	No data available	
Evaporation Rate:	No data available	Viscosity:	No data available	

Status: Revised Section(s) Revised: All Revision Date: 06/01/2015 Page 3 of 6



Flammability:	Not applicable	Volatility:	Not applicable
Upper/lower Flammability or explosive limits	Not applicable		

SECTION 10	STABILITY AND REACTIVITY	
Chemical Stability:	Stable under normal conditions of storage and handling.	
Conditions to Avoid:	Mildly corrosive to metals in the presence of moisture.	
Incompatible Materials:	Avoid contact with hot nitric acid, may cause evolution of toxic nitrosyl chloride. Contact with other strong acids may produce irritating hydrogen chloride gas. KCI may react violently with bromine trifluoride and may explode if mixed with potassium permanganate and sulfuric acid. NaCl can react with most noble metals, such as iron or steel, building materials (such as cement), bromine, or trifluoride. A potentially explosive reaction may occur if NaCl is mixed with dichloromaleic anhydride and urea. Electrolysis of mixtures containing NaCl and nitrogen compounds may form explosive nitrogen trichloride.	
Hazardous Decomposition Products:	Combustion can yield oxides of sulfur when heated above 1000°F (537°C).	
Corrosiveness:	Mildly corrosive to metals in the presence of moisture.	
Hazardous Polymerization:	Will not occur	

SECTION 11	TOXICOLOGICAL INFORMATION			
Substance:	Potassium Magnesium Sulfate			
Acute Oral Toxicity:	No data available			
Acute Inhalation Toxicity:	No data available			
Acute Dermal Toxicity:	No data available			
Substance:	Sodium Chloride			
Acute Oral Toxicity:	LD_{50} (rat, oral) > 3000 mg/kg LD_{50} (mouse, oral) > 4000 mg/kg			
Acute Inhalation Toxicity:	LC_{50} (rat) > 42 g/m ³ / 1 hour			
Acute Dermal Toxicity:	No data available			
Mutagenesis:	No data available Target Organ No data available			
Developmental Toxicity:	No data available Carcinogenicity No data available			

SECTION 12	ECOLOGICAL INFORMATION
Ecotoxicology:	When dissolved in water, sodium chloride creates an elevated level of salinity that may be harmful to fresh water aquatic species and to plants that are not salt-tolerant.



SECTION 13	DISPOSAL CONSIDERATIONS
	Recover or recycle if possible. Properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material. Prevent material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways.

SECTION 14	TRANSPORT INFO			
Regulatory Status:		Not regulated		
Identification Number:		HTS 3104.90.01		
Hazard Class:		Not applicable		
Proper Shipping Name		Not applicable		
Packing Group		Not applicable		
DOT Emergency Response	e Guide Number:	Not applicable		
Transport in bulk according to Annex II of MARPOL 73/78 ⁹ and the IBC Code ¹⁰ :		Not applicable		
MARPOL Annex V:		Non-HME		
IMO/IMDG:		Not applicable		

SECTION 15	REGULATORY INFORMATION					
CERCLA:	Not listed					
RCRA 261.33:	Not listed					
SARA TITLE III: (Exemptions at 40 CFR, Part 370 may apply for	Section 302/304:	Not listed	RQ: No		TPQ: No	
	Section 311/312:					
agricultural use, or for quantities of less than	Acute: No	Chronic: No	Fire: No	Pressure: No	Reactivity: No	
10,000 pounds on-site.)	Section 313: Not listed					
NTP, IARC, OSHA:	This material has not been identified as a carcinogen by NTP, IARC, or OSHA.					
Canada DSL and NDSL:	DSL: Yes NDSL: Not listed					
TSCA:	Listed on the TSCA Inventory					
CA Proposition 65: (Health & Safety Code Section 25249.5)	Warning: This product contains substances known to the State of California to cause cancer and/or birth defects or other reproductive harm.					
WHMIS:	WHMIS 2015 This SDS has been prepared according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR. WHMIS 1988 (Repealed) Classifications and/or symbols from the Controlled Products Regulations (CPR) are included in the Other Hazardous Classifications in Section 16 for reference.					

Status: Revised Section(s) Revised: All Revision Date: 06/01/2015 Page **5** of **6**



SECTION 16	OTHER INFORMATION						
Disclaimer:	The information in this document is believed to be correct as of the date issued. HOWEVER, MOSAIC MAKES NO GUARANTEE, REPRESENTATION, OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO THE USE OF THIS PRODUCT. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application and assumes the risk of use thereof. The conditions and use of this product are beyond the control of Mosaic, and Mosaic disclaims any liability for loss or damage incurred in connection with the use or misuse of this product. Each user should review the recommended industrial hygiene and safe handling procedures in the specific context of the intended use and determine whether they are appropriate.						
Preparation:	The preparation of this SDS was in accordance with ANSI Z400.1-2010.						
Revision Date:	June 1, 2015						
Sections Revised:	All						
SDS Number:	MOS 100042						
References:	Globally Harmonized System of Classification and Labelling of Chemicals (GHS) – 4 th Edition 2011 OSHA Hazard Communication Standard, 2012 MARPOL Annex V; The Fertilizer Institute (TFI), 2003; TOXNET Tomes, Toxnet, Grant (4th Ed.), RTECS NFPA HAZARD CLASS HMIS HAZARD CLASS WHMIS 1988 (CPR)						
	- NITATIAEAN	T	TIMIO TIAZARO GEAGO		HAZARD CLASS		
	Health:	1	Health:	1	Symbol	N/A	
	Flammability:	0	Flammability:	0			
	Instability:	0	Physical Hazard:	0	Classification	Not WHMIS Controlled	
Other Hazard Classifications:	Special Hazard:	None	PPE:	Section 8	Sub Class	N/A	
	WHMIS 2015 (HPR) HAZARD CLASS						
	Signal Word	N/A	1				
	Symbol	N/A					
	Classification	Not WHMIS Controlled					
	Hazard Statements	N/A					